

SNR 7314BGM angular contact ball bearings

SNR 7314BGM angular contact ball bearings Product Brochures , 182.563 mm da Manufacturing Service . Get Your 95.809 mm Ca Free.

da	182.563 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	309.575 mm
ba	74.612 mm
H	358.775 mm
H1	179.4 mm
H2	69.85 mm
L	628.65 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	49.212 mm
Housing	SSAFS 040 KA
Bearing	23040 CCK/W33
Adapter sleeve assembly	SNW 3040×7.3/16
Stabilizing ring	2 x 38151-40
Taconite seal	TER 159
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	425 r/min

P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	133 kN
Pa	48.9 kN
Mass pillow block	160 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	878.85 g