

SNR EC42217S01H206 tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your SNR EC42217S01H206 tapered roller bearings needs – including routine maintenance, major repairs, warranty service, and 0.0 Inventory equipment inspections.

| | |
|---------------------------|---------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 14.528 |
| EAN | 0883450198943 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 4 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Steel |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 3/4 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22217 |
| Seals | Triple Lip Nitrile Rubber |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Inch |
| Other Features | Double Row Extreme Duty |

| | |
|-------------------------------|--|
| Long Description | 4 Bolt Pillow Block; 3" Bore; 4" Base to Center Height; Tapered Adapter Sleeve Mount; Sphe |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | TAPK17K300SM |
| Weight / LBS | 37 |
| B | 4 Inch 101.6 Millimeter |
| Nominal Bolt Center to Center | 11.5 Inch 292.1 Millimeter |
| D | 3.23 Inch 82.042 Millimeter |
| Bolt Spacing Maximum | 12.19 Inch 309.626Millimeter |
| Bolt Spacing Minimum | 10.81 Inch 274.574Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| d | 3 Inch 76.2 Millimeter |