

# SNR ES207-23 deep groove ball bearings

Various types and sizes to accommodate 104.775 mm da your SNR ES207-23 deep groove ball bearings requirements.

da	104.775 mm
Da	259.999 mm
Ca	95.809 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	67.469 mm
H	320.675 mm
H1	160.325 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAF 624
Bearing	22324 CCK/W33
Adapter sleeve assembly	SNW 124×4.1/8

Stabilizing ring	SR-0-24
Labyrinth ring	2 x LOR 112
End plug (suffix Y)	EPR 14
Bearing limiting speed	2600 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	30.9 kN
Mass pillow block	93.5 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g