

SNR FC35080 tapered roller bearings

Online shopping SNR FC35080 tapered roller bearings from 15 Outer Diameter (mm) a great selection at Store. ... 32x15x9 Size (mm) Accessories.

Size (mm)	32x15x9
Bore Diameter (mm)	32
Outer Diameter (mm)	15
Width (mm)	9
d	15 mm
D	32 mm
B	9 mm
d1	20.6 mm
d2	20.6 mm
D2	29.2 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.2 mm
a	10.1 mm
da – min.	17 mm
da – max.	20.2 mm
db – min.	17 mm
db – max.	20.2 mm
Da – max.	30 mm
Db – max.	30.6 mm
ra – max.	0.3 mm
rb – max.	0.2 mm
Basic dynamic load rating – C	4.9 kN

Basic static load rating – C0	2.3 kN
Fatigue load limit – Pu	0.098 kN
Limiting speed for grease lubrication	50000 r/min
Ball – Dw	4.762 mm
Ball – z	12
Calculation factor – e	0.68
Calculation factor – Y2	1.41
Calculation factor – Y0	0.76
Calculation factor – X2	0.67
Calculation factor – Y1	0.92
Preload class A – GA	30 N
Preload class B – GB	60 N
Preload class C – GC	120 N
Preload class D – GD	240 N
Calculation factor – f	1.03
Calculation factor – f1	0.99
Calculation factor – f2A	1
Calculation factor – f2B	1.02
Calculation factor – f2C	1.05
Calculation factor – f2D	1.08
Calculation factor – fHC	1
Preload class A	41 N/micron
Preload class B	53 N/micron
Preload class C	69 N/micron
Preload class D	92 N/micron
r1,2 min.	0.3 mm
r3,4 min.	0.2 mm
da min.	17 mm
da max.	20.2 mm

db min.	17 mm
db max.	20.2 mm
Da max.	30 mm
Db max.	30.6 mm
ra max.	0.3 mm
rb max.	0.2 mm
Basic dynamic load rating C	4.94 kN
Basic static load rating C0	2.32 kN
Fatigue load limit Pu	0.098 kN
Attainable speed for grease lubrication	50000 r/min
Ball diameter Dw	4.762 mm
Number of balls z	12
Preload class A GA	30 N
Static axial stiffness, preload class A	41 N/μm
Preload class B GB	60 N
Static axial stiffness, preload class B	53 N/μm
Preload class C GC	120 N
Static axial stiffness, preload class C	69 N/μm
Preload class D GD	240 N
Static axial stiffness, preload class D	92 N/μm
Calculation factor f	1.03
Calculation factor f1	0.99
Calculation factor f2A	1
Calculation factor f2B	1.02
Calculation factor f2C	1.05
Calculation factor f2D	1.08
Calculation factor fHC	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y2	0.87

Calculation factor (single, tandem) Y0	0.38
Calculation factor (single, tandem) X2	0.41
Calculation factor (back-to-back, face-to-face) Y1	0.92
Calculation factor (back-to-back, face-to-face) Y2	1.41
Calculation factor (back-to-back, face-to-face) Y0	0.76
Calculation factor (back-to-back, face-to-face) X2	0.67
Mass bearing	0.03 kg