

# SNR NU322EG15 cylindrical roller bearings

SNR NU322EG15 cylindrical roller bearings with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

da	93.662 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	165.1 mm
ba	42.069 mm
H	239.316 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAF 522
Bearing	1222 K

Adapter sleeve assembly	SNW 22×3.11/16
Stabilizing ring	2 x SR-1522
Labyrinth ring	2 x LOR 557
PosiTrac Plus contact element	2 x B10724-109
End plug (suffix Y)	EPR 13
Max. speed for PosiTrac Plus seal	1450 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	12.5 kN
Mass pillow block	33.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g