

SNR NU328EM cylindrical roller bearings

Shop SNR NU328EM cylindrical roller bearings huge online discount inventory. and Import machinery parts 22x44x12 Size (mm) your car needs with Free Shipping and Free Extended Warranty.

Size (mm)	22x44x12
Bore Diameter (mm)	22
Outer Diameter (mm)	44
Width (mm)	12
d	22 mm
D	44 mm
B	12 mm
C	12 mm
r min.	0,6 mm
da min.	26 mm
da max	26,5 mm
Da max.	40 mm
ra max.	0,6 mm
Weight	0,074 Kg
Basic dynamic load rating (C)	9,4 kN
Basic static load rating (C0)	5,05 kN
(Grease) Lubrication Speed	17 000 r/min
(Oil) Lubrication Speed	20 000 r/min
rs min	0.6 mm
Radial clearance class	CN
Mass	0.07 kg

Dynamic load, C	9.4 kN
Static load, C0	5.05 kN
Fatigue limit load, Cu	0.23 kN
f0	13.9
Nlim (oil)	20,000 rpm
Nlim (grease)	17,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.76 Hz
Characteristic outer ring frequency, BPF0	3.59 Hz
Characteristic inner ring frequency, BRFI	5.41 Hz
da min	26 mm
Da max	40 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.07
EAN	4547359312423
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No

Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	22MM Bore; 44MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	60/22
Weight / LBS	0.163
Bore	0.866 Inch 22 Millimeter
Outside Diameter	1.732 Inch 44 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
bore diameter:	22 mm
finish/coating:	Uncoated
outside diameter:	44 mm
bearing material:	High Carbon Chrome Steel
overall width:	12 mm
cage material:	Steel
bore type:	Round
inner ring width:	12 mm
closure type:	Open
outer ring width:	12 mm

row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	17000 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	20000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	20000 RPM
dynamic load capacity:	9400 N
series:	60
static load capacity:	5050 N
manufacturer product page:	Click here
precision rating:	Class 0