

SNR R150.34 wheel bearings

SNR R150.34 wheel bearings Manufacturers , Online Wholesale Suppliers ! 69.85×31.75×17.462 Size (mm)

Size (mm)	69.85×31.75×17.462
Bore Diameter (mm)	69,85
Outer Diameter (mm)	31,75
Width (mm)	17,462
d	31.75 mm
D	69.85 mm
B	17.462 mm
d1	42.3 mm
D2	57.1 mm
r1,2 – min.	1.6 mm
da – min.	39 mm
Da – max.	62 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	22.5 kN
Basic static load rating – C0	13.2 kN
Fatigue load limit – Pu	0.55 kN
Reference speed	20000 r/min
Limiting speed	14000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.304

EAN	7316577017734
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Inch
Long Description	1-1/4" Bore; 2-3/4" Outside Diameter; 11/16" Outer Race Width; Open; Ball Bearing; AB
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	RLS 10
Weight / LBS	0.67
Outer Race Width	0.688 Inch 17.475 Millimeter
Bore	1.25 Inch 31.75 Millimeter
Outside Diameter	2.75 Inch 69.85 Millimeter
bore diameter:	1.2500 in
static load capacity:	13.2 kN
outside diameter:	2.7500 in
precision rating:	Not Rated
overall width:	0.6875 in
finish/coating:	Uncoated

bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	17.462 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1.5 mm
internal clearance:	C0
maximum rpm:	14000 RPM
dynamic load capacity:	22.5 kN
series:	RLS
d1 ≈	42.3 mm
D2 ≈	57.1 mm
r1,2 min.	1.6 mm
da min.	39 mm
Da max.	62 mm
ra max.	1.5 mm
Basic dynamic load rating C	22.5 kN
Basic static load rating C0	13.2 kN
Fatigue load limit Pu	0.55 kN
Calculation factor kr	0.025
Calculation factor f0	14
Mass bearing	0.3 kg