

# SNR UCFLZ202 bearing units

What 42.799 mm Ca is the best 150 mm Da place to buy SNR UCFLZ202 bearing units online? 76.2 mm da Manufacturing Service .

|                         |             |
|-------------------------|-------------|
| da                      | 76.2 mm     |
| Da                      | 150 mm      |
| Ca                      | 42.799 mm   |
| A1                      | 88.9 mm     |
| A2                      | 127 mm      |
| ba                      | 31.75 mm    |
| H                       | 180.975 mm  |
| H1                      | 95.25 mm    |
| H2                      | 31.75 mm    |
| J min.                  | 250.825 mm  |
| J max.                  | 279.4 mm    |
| L                       | 330.2 mm    |
| N1                      | 22.225 mm   |
| R1                      | 53.975 mm   |
| R2                      | 22.225 mm   |
| RG                      | 3/8 NPT     |
| PG                      | 1/8 NPT     |
| h                       | 36.513 mm   |
| Housing                 | SAF 517     |
| Bearing                 | 1217 K      |
| Adapter sleeve assembly | SNW 17×3    |
| Stabilizing ring        | 2 x SR-1517 |
| Labyrinth ring          | 2 x LOR 54  |

|  |                |
|--|----------------|
| PosiTrac Plus contact element          | 2 x B10724-53  |
| End plug (suffix Y)                    | EPR 9          |
| Max. speed for PosiTrac Plus seal      | 1950 r/min     |
| P60°                                   | 84.5 kN        |
| P90°                                   | 50.7 kN        |
| P120°                                  | 31.6 kN        |
| P150°                                  | 28.5 kN        |
| P180°                                  | 34.7 kN        |
| Pa                                     | 7.12 kN        |
| Mass pillow block                      | 17.9 kg        |
| Cap bolt                               | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 149.1 N·m      |
| Cap bolt, SAE grade                    | 5              |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 218.29 g       |