

SNR UCPG212 bearing units

What are the dimensions of a SNR UCPG212 bearing units? 110 Outer Diameter (mm) Manufacturing Service . Get 70x110x40 Size (mm) Your 70 Bore Diameter (mm) Free, Instant Quote

| | |
|----------------------|------------------|
| Size (mm) | 70x110x40 |
| Bore Diameter (mm) | 70 |
| Outer Diameter (mm) | 110 |
| Width (mm) | 40 |
| d | 70 mm |
| D | 110 mm |
| B | 40 mm |
| C | 40 mm |
| Angle (α) | 15 ° |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.18 |
| EAN | 4547359432558 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 7 ISO P4 |
| Material – Ball | Steel |
| Number of Bearings | 2 (1 Pair) |
| Contact Angle | 15 Degree |
| Preload | Light |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Nylon |

| | |
|--------------------------|--|
| Rolling Element | Ball Bearing |
| Mounting Arrangement | Duplex-Back to Back |
| Flush Ground | Yes |
| Inch – Metric | Metric |
| Other Features | Single Row Angular Contact |
| Long Description | 70MM Bore; 110MM Outside Diameter; 40MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer Item Number | 7014CDB/GNP4 |
| Weight / LBS | 2.59 |
| Bore | 2.756 Inch 70 Millimeter |
| Outside Diameter | 4.331 Inch 110 Millimeter |
| Width | 1.575 Inch 40 Millimeter |
| bore diameter: | 70 mm |
| cage material: | Nylon |
| outside diameter: | 110 mm |
| finish/coating: | Uncoated |
| overall width: | 40 mm |
| inner ring width: | 20 mm |
| contact angle: | 15 ° |
| maximum rpm (oil): | 16640 rpm |
| duplex type: | Back to Back |
| maximum rpm (grease): | 10400 rpm |
| closure type: | Open |
| outer ring width: | 20 mm |

| | |
|------------------------------|----------------------------|
| operating temperature range: | -40 to 120 °C |
| fillet radius: | 1.1 mm |
| bearing material: | High Carbon Chrome Steel |
| manufacturer product page: | Click here |
| precision rating: | ISO Class 4 |