

Supply Slewing Ring for Stacker and Reclaimer

With over N/A Minimum Buy Quantity 10170 full-service stores, our Supply Slewing Ring for Stacker and Reclaimer inventory is extensive and 0.0 Inventory our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	10.105
EAN	7316576603716
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AHX3128 (Specify bore)
Withdrawal Nut	KM30
Inch – Metric	Metric
Long Description	140MM Tapered Bore; 225MM Outside Diameter; 68MM Width; C3-Loose Clearance; Adapter Mount; Double Ro

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	22.258
d	5.512 Inch 140 Millimeter
B	2.677 Inch 68 Millimeter
Adapter Part Number	SNW3128 H3128 HA3128 HE3128 (Specify bore) Inch H3128 (Specify bore) Millimeter
D	8.858 Inch 225 Millimeter
bore diameter:	140 mm
maximum rpm:	2800 RPM
outside diameter:	225 mm
operating temperature range:	Maximum of +390 °F
overall width:	68 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	68 mm

dynamic load capacity:	630 kN
fillet radius:	2 mm
static load capacity:	900 kN
series:	231