

SX011832 INA 0.010 mm / Running accuracy. axial 160x200x20mm Complex bearings

Bearing number	SX011832
Size (mm)	160x200x20
Brand	INA
Bore Diameter (mm)	160
Outer Diameter (mm)	200
Width (mm)	20
$d_i - 160 \text{ mm} /$ Tolerance: K6 +0,004 / -0,021	160 mm / Tolerance: K6 +0.004 / 0.021
$D_a - 200 \text{ mm} /$ Tolerance: h6 -0,029	200 mm / Tolerance: h6 0.029
H - 20 mm / Tolerance: +/-0,12	20 mm / Tolerance: +/-0.12
D_i	180.8 mm
D_M	180 mm
d_a	179.2 mm
h - 20 mm / Tolerance: E8 -0,025	20 mm / Tolerance: E8 0.025
r_{min}	1.1 mm
S	1.5 mm
m	1.7 kg / Weight
	0.015 mm / Running accuracy. radial
	0.010 mm / Running accuracy. axial

$S_{r \min}$	0.005 mm / Min. radial bearing clearance
$S_{r \max}$	0.020 mm / Max. radial bearing clearance
$S_{k \min}$	0.010 mm / Min. axial tilting clearance
$S_{k \max}$	0.04 mm / Max. axial tilting clearance
RLO_{\max}	0.004 mm / Low clearance: Radial clearance
RLO_{\max}	0.008 mm / Low clearance: Preload
VSP_{\min}	0.005 mm / Min. bearing preload
VSP_{\max}	0.020 mm / Max. bearing preload
C_a	68000 N / Dynamic load rating (axial)
$C_{\theta a}$	275000 N / Static load rating (axial)
C_r	48500 N / Dynamic load rating (radial)(for radial load only)
$C_{\theta r}$	111000 N / Static load rating (radial)(for radial load only)
$n_{G \text{ oil}}$	850 1/min / Limiting speed for oil lubrication with normal clearance
$n_{G \text{ Fett}}$	425 1/min / Limiting speed for grease lubrication with normal clearance
$n_{G \text{ oil}}$	425 1/min / Limiting speed for oil lubrication with preload
Category	Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	1.916
EAN	4012802443165

Product Group – BDI

B00234