

T2ED095 KOYO 95x160x46mm r(min) 3 Tapered roller bearings

| | |
|-------------------------------|-----------|
| Bearing number | T2ED095 |
| Size (mm) | 95x160x46 |
| Brand | KOYO |
| Bore Diameter (mm) | 95 |
| Outer Diameter (mm) | 160 |
| Width (mm) | 46 |
| d | 95 mm |
| D | 160 mm |
| T | 46 mm |
| B | 46 mm |
| C | 38 mm |
| a | 34.6 mm |
| r min. | 3 mm |
| r2 min. | 3 mm |
| da min. | 109 mm |
| da max | 107 mm |
| Da min | 140 mm |
| Da max. | 146 mm |
| Db min. | 152 mm |
| ra max. | 2.5 mm |
| rb max. | 2.5 mm |
| Weight | 3.62 Kg |
| Basic dynamic load rating (C) | 281 kN |
| Basic static load rating (C0) | 427 kN |

| | |
|----------------------------|------------|
| (Grease) Lubrication Speed | 2300 r/min |
| (Oil) Lubrication Speed | 3100 r/min |
| Calculation factor (e) | 0.34 |
| Calculation factor (Y0) | 0.97 |
| Bearing No. | T2ED095 |
| r(min) | 3 |
| r1(min) | 3 |
| Cr | 353 |
| C0r | 427 |
| Cu | 56.4 |
| Grease lub. | 2300 |
| Oil lub. | 3100 |
| a(mm) | 34.6 |
| da(min) | 109 |
| db(max) | 107 |
| Da(max) | 146 |
| Da(min) | 140 |
| Db(min) | 152 |
| Sa(min) | 7 |
| Sb(min) | 8 |
| ra(max) | 2.5 |
| rb(max) | 2.5 |
| e | 0.34 |
| Y1 | 1.77 |
| Y0 | 0.97 |
| (Refer.) Mass (kg) | 3.62 |