

# T2ED095 NSK DI\_ 112.36

## 95x160x46mm Tapered roller bearings

Bearing number	T2ED095
ISO 4269	9516046
ISO 4269-1	
Bore diameter (mm)	95
Outer diameter (mm)	160
Width (mm)	46
D	95 mm
d	160 mm
B	46 mm
C	38 mm
A	24.2 mm
r min.	3 mm
r max.	2 mm
DA max.	113 mm
DA min.	145 mm
DB max.	148 mm
DB min.	188 mm
DC max.	153 mm
DC min.	2.5 mm
Weight	3.74 kg
Basic dynamic load rating (C)	283 kN
Basic static load rating (C0)	442 kN
Basic rating life (L10)	10 000 000 km
Life at 100% speed	2000 h/rev
Life at 100% speed	3000 h/rev
Factor (a1)	6.34
Factor (a2)	6.87
Factor (a3)	1
Factor (a4)	3
ISO 2818	
ISO 2818-1	
ISO 2818-2	
ISO 2818-3	
ISO 2818-4	
ISO 2818-5	
ISO 2818-6	
ISO 2818-7	
ISO 2818-8	
ISO 2818-9	
ISO 2818-10	
ISO 2818-11	
ISO 2818-12	
ISO 2818-13	
ISO 2818-14	
ISO 2818-15	
ISO 2818-16	
ISO 2818-17	
ISO 2818-18	
ISO 2818-19	
ISO 2818-20	
ISO 2818-21	
ISO 2818-22	
ISO 2818-23	
ISO 2818-24	
ISO 2818-25	
ISO 2818-26	
ISO 2818-27	
ISO 2818-28	
ISO 2818-29	
ISO 2818-30	
ISO 2818-31	
ISO 2818-32	
ISO 2818-33	
ISO 2818-34	
ISO 2818-35	
ISO 2818-36	
ISO 2818-37	
ISO 2818-38	
ISO 2818-39	
ISO 2818-40	
ISO 2818-41	
ISO 2818-42	
ISO 2818-43	
ISO 2818-44	
ISO 2818-45	
ISO 2818-46	
ISO 2818-47	
ISO 2818-48	
ISO 2818-49	
ISO 2818-50	
ISO 2818-51	
ISO 2818-52	
ISO 2818-53	
ISO 2818-54	
ISO 2818-55	
ISO 2818-56	
ISO 2818-57	
ISO 2818-58	
ISO 2818-59	
ISO 2818-60	
ISO 2818-61	
ISO 2818-62	
ISO 2818-63	
ISO 2818-64	
ISO 2818-65	
ISO 2818-66	
ISO 2818-67	
ISO 2818-68	
ISO 2818-69	
ISO 2818-70	
ISO 2818-71	
ISO 2818-72	
ISO 2818-73	
ISO 2818-74	
ISO 2818-75	
ISO 2818-76	
ISO 2818-77	
ISO 2818-78	
ISO 2818-79	
ISO 2818-80	
ISO 2818-81	
ISO 2818-82	
ISO 2818-83	
ISO 2818-84	
ISO 2818-85	
ISO 2818-86	
ISO 2818-87	
ISO 2818-88	
ISO 2818-89	
ISO 2818-90	
ISO 2818-91	
ISO 2818-92	
ISO 2818-93	
ISO 2818-94	
ISO 2818-95	
ISO 2818-96	
ISO 2818-97	
ISO 2818-98	
ISO 2818-99	
ISO 2818-100	