

T2EE060 KOYO 60x115x40mm a 27.6mm Tapered roller bearings

| | |
|-------------------------------|-----------|
| Bearing number | T2EE060 |
| Size (mm) | 60x115x40 |
| Brand | KOYO |
| Bore Diameter (mm) | 60 |
| Outer Diameter (mm) | 115 |
| Width (mm) | 40 |
| d | 60 mm |
| D | 115 mm |
| T | 40 mm |
| B | 39 mm |
| C | 33 mm |
| a | 27.6 mm |
| r min. | 2.5 mm |
| r2 min. | 2.5 mm |
| da min. | 72 mm |
| da max | 70 mm |
| Da min | 98 mm |
| Da max. | 103 mm |
| Db min. | 109 mm |
| ra max. | 2 mm |
| rb max. | 2 mm |
| Weight | 1.8 Kg |
| Basic dynamic load rating (C) | 183 kN |
| Basic static load rating (C0) | 242 kN |

| | |
|----------------------------|------------|
| (Grease) Lubrication Speed | 3400 r/min |
| (Oil) Lubrication Speed | 4600 r/min |
| Calculation factor (e) | 0.33 |
| Calculation factor (Y0) | 0.99 |
| Bearing No. | T2EE060 |
| r(min) | 2.5 |
| r1(min) | 2.5 |
| Cr | 229 |
| C0r | 242 |
| Cu | 37.7 |
| Grease lub. | 3400 |
| Oil lub. | 4600 |
| a(mm) | 27.6 |
| da(min) | 72 |
| db(max) | 70 |
| Da(max) | 103 |
| Da(min) | 98 |
| Db(min) | 109 |
| Sa(min) | 6 |
| Sb(min) | 7 |
| ra(max) | 2 |
| rb(max) | 2 |
| e | 0.33 |
| Y1 | 1.80 |
| Y0 | 0.99 |
| (Refer.) Mass (kg) | 1.80 |