

# Three Row Roller Slewing Ring Bearings for Bulldozer

Various 0.0 Inventory types and sizes to accommodate your SKF Manufacturer Name Three Row Roller Slewing Ring Bearings for Bulldozer requirements.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	22.47
EAN	7316576663888
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22220
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Double Row   Heavy Duty   Single Collar   Locating Bearing   Open End   With Set Screw

Long Description	4 Bolt Pillow Block; 3-15/16" Bore; 4-1/4" Base to Center Height; Concentric Collar Mount;
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	FSYE 3.15/16 H
Weight / LBS	49.5
B	4.25 Inch   107.95 Millimeter
D	4.594 Inch   116.688 Millimeter
Nominal Bolt Center to Center	12.5 Inch   317.5 Millimeter
Bolt Spacing Maximum	13 Inch   330.2Millimeter
Bolt Spacing Minimum	12 Inch   304.8Millimeter
d	3.938 Inch   100.025 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
bore diameter:	3.9375 in
bolt center-to-center length:	12-1/2 in
overall length:	15.2500 in
base width:	4-1/2 in
overall height:	8.5625 in
expansion type:	Non-Expansion Bearing (Fixed)
mounting:	Four-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round
radial dynamic load capacity:	95000 lbf
housing construction:	Solid Pillow Block

radial static load capacity:	110000 lbf
base to bore centerline:	4.2500 in
maximum rpm:	1250 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	FSYE
locking device:	Concentric Collar
replacement bearing:	22220