

# Timken 16150/16284B tapered roller bearings

Timken 16150/16284B tapered roller bearings Product Brochures , Manufacturing Service . Get 0.0 Inventory Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 22.97  |
| EAN                       | 0662461364154  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | USI5000A-311-C   |
| Seals                     | Double Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 2 Bolt Pillow Block; 3-11/16" Bore; 4-1/8" Base to Center Height; Adapter Sleeve Mount; Sp |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | USRB5000A-311-C                 |
| Manufacturer Internal Number  | 737585                          |
| Weight / LBS                  | 50.6                            |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| d                             | 3.688 Inch   93.675 Millimeter  |
| Nominal Bolt Center to Center | 10.9 Inch   276.9 Millimeter    |
| B                             | 4.125 Inch   104.775 Millimeter |
| Bolt Spacing Maximum          | 11.75 Inch   298.45Millimeter   |
| D                             | 5.938 Inch   150.825 Millimeter |
| Bolt Spacing Minimum          | 10 Inch   254Millimeter         |