

Timken 180RN30 cylindrical roller bearings

What are the dimensions of a Timken 180RN30 cylindrical roller bearings? Manufacturing Service 266.7 mm da . Get Your Free, Instant Quote

da	266.7 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	315.119 mm
ba	100.806 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	73.025 mm
Housing	SAFS 056 KAUA
Bearing	23056 CCK/W33
Adapter sleeve assembly	SNP 3056×10.1/2

Stabilizing ring	2 x A8819
Labyrinth ring	2 x LOR 519
End plug (suffix Y)	X-5217-2
Bearing limiting speed	1600 r/min
P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	89 kN
Mass pillow block	298 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g