

Timken 19138X/19283 tapered roller bearings

170 Million used Timken 19138X/19283 tapered roller bearings instantly searchable. Shop our 40 Bore Diameter (mm) large selection of parts based on brand, 75 Outer Diameter (mm) price, 40x75x26 Size (mm) description, and location. Order the with stock ...

| | |
|---------------------|----------|
| Size (mm) | 40x75x26 |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 75 |
| Width (mm) | 26 |
| d | 40 mm |
| D | 75 mm |
| T | 26 mm |
| B | 26 mm |
| C | 20,5 mm |
| a | 18,3 mm |
| r min. | 1,5 mm |
| r2 min. | 1,5 mm |
| da min. | 48,5 mm |
| da max | 47 mm |
| Da min | 65 mm |
| Da max. | 66,5 mm |
| Db min. | 71 mm |
| ra max. | 1,5 mm |
| rb max. | 1,5 mm |
| Weight | 0,508 Kg |

| | |
|-------------------------------|------------|
| Basic dynamic load rating (C) | 82,2 kN |
| Basic static load rating (C0) | 108 kN |
| (Grease) Lubrication Speed | 5200 r/min |
| (Oil) Lubrication Speed | 6900 r/min |
| Calculation factor (e) | 0,36 |
| Calculation factor (Y0) | 0,93 |
| Bearing No. | 33108JR |
| r(min) | 1.5 |
| r1(min) | 1.5 |
| Cr | 103 |
| C0r | 108 |
| Cu | 16.1 |
| Grease lub. | 5200 |
| Oil lub. | 6900 |
| a(mm) | 18.3 |
| da(min) | 48.5 |
| db(max) | 47 |
| Da(max) | 66.5 |
| Da(min) | 65 |
| Db(min) | 71 |
| Sa(min) | 4 |
| Sb(min) | 5.5 |
| ra(max) | 1.5 |
| rb(max) | 1.5 |
| e | 0.36 |
| Y1 | 1.69 |
| Y0 | 0.93 |
| (Refer.) Mass (kg) | 0.508 |