

Timken 210RJ91 cylindrical roller bearings

High Quality Timken 210RJ91 cylindrical roller bearings. Competitive Pricing. Accept Small Order. Easy and 160x340x68 Size (mm) Fast Shipping.

| | |
|------------------------|------------|
| Size (mm) | 160x340x68 |
| Bore Diameter (mm) | 160,000 |
| Outer Diameter (mm) | 340,000 |
| Width (mm) | 68,000 |
| d | 160,000 mm |
| D | 340,000 mm |
| B | 68,000 mm |
| C | 68,000 mm |
| d1 | 231 mm |
| d2 | 181.7 mm |
| D1 | 270 mm |
| D2 | 318.8 mm |
| a | 139 mm |
| Contact angle α | 40 ° |
| rs min | 4 mm |
| rls min | 1.5 mm |
| Radial clearance class | CN |
| Mass | 30.5 kg |
| Dynamic load, C | 354 kN |
| Static load, C0 | 451 kN |
| Fatigue limit load, Cu | 13 kN |
| Nref | 2,100 rpm |

| | |
|---|-----------|
| Nlim | 2,500 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.41 Hz |
| Characteristic rolling element frequency, BSF | 4.37 Hz |
| Characteristic outer ring frequency, BPF0 | 5.39 Hz |
| Characteristic inner ring frequency, BRFI | 7.61 Hz |
| da min | 178 mm |
| db min | 178 mm |
| Da max | 322 mm |
| Db max | 331.5 mm |
| r1a max | 1.5 mm |
| ra max | 3 mm |