

# Timken 246X/242 tapered roller bearings

Welcome to the 0.0 Inventory Timken 246X/242 tapered roller bearings online seller.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 13.51  |
| EAN                       | 0782475654710  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Set Screw  |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 18 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-SCM-85M  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Metric   |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>85MM Bore; 218.4MM Bolt<br>Circle; 154.8MM Bolt Spacing;<br>1 Piece Solid; |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Single Row   Medium Duty  <br>Wide Inner Race |
| UNSPSC                                | 31171501                                      |
| Harmonized Tariff Code                | 8483.20.40.40                                 |
| Noun                                  | Bearing                                       |
| Keyword String                        | Flanged                                       |
| Manufacturer Item Number              | FC-SCM-85M                                    |
| Manufacturer Internal Number          | 125949  |
| Weight / LBS                          | 29.762  |
| Cartridge Pilot Diameter              | 7.374 Inch   187.3 Millimeter                 |
| Nominal Bolt Circle Diameter<br>Round | 8.6 Inch   218.4 Millimeter                   |
| D                                     | 2.484 Inch   63.1 Millimeter                  |
| Cartridge Pilot Depth                 | 1.374 Inch   34.9 Millimeter                  |
| Bolt Spacing                          | 6.094 Inch   154.8 Millimeter                 |
| d                                     | 3.346 Inch   85 Millimeter                    |