

Timken 24780/24722 tapered roller bearings

We Provide Extensive Timken 24780/24722 tapered roller bearings Selection 70 mm V And Competitive Wholesale Pricing.
25 Bore Diameter (mm)

Bore Diameter (mm)	25
d	25 mm
V	70 mm
U	42,5 mm
Thread (Q)	Rp1/8
d3	37,5 mm
A	26,5 mm
A1	11 mm
B1	31 mm
H	124 mm
J	99 mm
L	70 mm
N	11,5 mm
A2	19 mm
Weight	0,58 Kg
Basic dynamic load rating (C)	14 kN
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.707
EAN	4012802837490
Product Group	M06110

Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	11.5 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE25NPPB
Seals	Double Lip Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	2 Bolt Flange Block; 25MM Bore; 99MM Bolt Circle; 99MM Bolt Spacing; 1 Piece Solid; Eccentric Collar
Other Features	Single Row With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	PCJT25N
Weight / LBS	1.544
Cartridge Pilot Depth	0 Inch 0 Millimeter
Bore	0.984 Inch 25 Millimeter
Length Thru Bore	1.22 Inch 31 Millimeter
Bolt Spacing	3.9 Inch 99 Millimeter
Nominal Bolt Circle Diameter Round	3.9 Inch 99 Millimeter

Cartridge Pilot Diameter	0 Inch 0 Millimeter
--------------------------	-----------------------