

# Timken 2558/2523-B tapered roller bearings

What is Timken 2558/2523-B tapered roller bearings in N/A Minimum Buy Quantity mechanical engineering? Manufacturing Service . Upload your CAD file 0.0 Inventory for an instant.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | IPTCI BEARINGS   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 1.82   |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | SA207-23G  |
| Seals                     | K Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Narrow Inner Race<br>  Low Base   |
| Long Description          | 2 Bolt Pillow Block; 1-7/16" Bore; 1-13/16" Base to Center Height; Eccentric Collar Mount; |
| UNSPSC                    | 31171511   |

|                               |                                |
|-------------------------------|--------------------------------|
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | SAPL 207 23 G                  |
| Weight / LBS                  | 4                              |
| Actual Bolt Center to Center  | 5 Inch   127Millimeter         |
| d                             | 1.438 Inch   36.525 Millimeter |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |
| D                             | 1.532 Inch   38.913 Millimeter |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |
| B                             | 1.813 Inch   46.05 Millimeter  |
| Nominal Bolt Center to Center | 5 Inch   127 Millimeter        |