

# Timken 25590/25521B tapered roller bearings

Our highly-skilled and factory-trained service experts have the 289.999 mm Da resources to help you with all your Timken 25590/25521B tapered roller bearings 174.625 mm da needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

da	174.625 mm
Da	289.999 mm
Ca	89.789 mm
A1	158.75 mm
A2	288.925 mm
ba	69.85 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	47.625 mm
Housing	SAFS 038 KA

Bearing	23038 CCK/W33
Adapter sleeve assembly	SNW 3038×6.7/8
Stabilizing ring	2 x 38151-38
Taconite seal	TER 154
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	440 r/min
P60°	345 kN
P90°	207 kN
P120°	133 kN
P150°	120 kN
P180°	145 kN
Pa	42.9 kN
Mass pillow block	121 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g