

Timken 2582/2525 tapered roller bearings

Advance Timken 2582/2525 tapered roller bearings 0.0 Inventory is your source for quality and N/A Minimum Buy Quantity accessories. shop online for home SKF Manufacturer Name delivery or pick up in one of our 10000 .

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.146
EAN	7316577612694
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AHX312 (Specify bore)
Withdrawal Nut	KM14
Inch – Metric	Metric
Long Description	60MM Tapered Bore; 110MM Outside Diameter; 28MM Width; C0-Medium Clearance; Adapter Mount; Double Ro

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	2.524
D	4.331 Inch 110 Millimeter
Adapter Part Number	SNW12 H312 HA312 HE312 HS312 (Specify Bore) Inch H312 (Specify bore) Millimeter
d	2.362 Inch 60 Millimeter
B	1.102 Inch 28 Millimeter
bore diameter:	60 mm
maximum rpm:	7500 RPM
outside diameter:	110 mm
operating temperature range:	Maximum of +390 °F
overall width:	28 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	28 mm

dynamic load capacity:	156 kN
fillet radius:	1.5 mm
static load capacity:	166 kN
series:	222