

Timken 26112/26300 tapered roller bearings

Timken 26112/26300 tapered roller bearings Industries and Applications ? We sell discount online as 360,000 Outer Diameter (mm) well as cheap machinery parts. 200x360x128 Size (mm)

Size (mm)	200x360x128
Bore Diameter (mm)	200,000
Outer Diameter (mm)	360,000
Width (mm)	128,000
d	200,000 mm
D	360,000 mm
H	128,000 mm
B	128 mm
D1	314.8 mm
rs min	4 mm
Number of lubrication holes	3
b	18.8 mm
k	9 mm
Associated sleeve reference	H2340
e	0.34
Y1	1.98
Y2	2.94
Y0	1.93
Radial clearance class	CN
Mass	55.8 kg
Dynamic load, C	2,250 kN

Static load, C_0	2,840 kN
Fatigue limit load, C_u	173 kN
N_{ref}	1,100 rpm
N_{lim}	1,700 rpm
Min operating temperature, T_{min}	-40 °C
Max operating temperature, T_{max}	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.21 Hz
Characteristic outer ring frequency, BPF0	7.62 Hz
Characteristic inner ring frequency, BRFI	10.38 Hz
$d_{a \min}$	217 mm
$D_{a \max}$	343 mm
$r_{a \max}$	3 mm