

# Timken 26118-S/26283-B tapered roller bearings

100% Authentic. Timken 26118-S/26283-B tapered roller bearings 55 Outer Diameter (mm) Highest 30x55x13 Size (mm) Quality. Certified Supplier.

Size (mm)	30x55x13
Bore Diameter (mm)	30
Outer Diameter (mm)	55
Width (mm)	13
d	30 mm
D	55 mm
B	13 mm
C	13 mm
rn	0,5 mm
a	2,08 mm
b	1,35 mm
r min.	1 mm
r $\theta$ max.	0,4 mm
D1	52,6 mm
da min.	35 mm
da max	36,5 mm
Da max.	50 mm
ra max.	1 mm
Weight	0,116 Kg
Basic dynamic load rating (C)	13,2 kN
Basic static load rating (C $\theta$ )	8,3 kN
(Grease) Lubrication Speed	13 000 r/min

(Oil) Lubrication Speed	15 000 r/min
SRI	3.61
hidYobi	6006N
LangID	1
ro	0.4
D_	55
SREX	0.04
B_	13
da min	35
hidTable	ecat_NSRDGB
Oil rpm	15000
SRE	3.79
mass	0.116
GRS rpm	13000
ra	1
SRIX	0.02
D_a	50
SRIN	0
C0	8.3
fo	14.7
SREN	0
DE_	49.844
Prod_Type3	DGBB_SR_N_OT
DA_	7.144
bomp	0
Z_	11
yobi	6006N
C_conv	13200
ALPHA_	0

SDM_	42.7
r	1
KBRG	6101
SBRG	10
DI_	35.556