

Timken 27684/27620-B tapered roller bearings

Various types and sizes to accommodate your Timken 27684/27620-B tapered roller bearings 0.0 Inventory requirements.

| | |
|----------------------------|---------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0883450504997 |
| Weight / US pound | 0.01 |
| Product Group | M06110 |
| Shaft Size | 2.6875 in |
| Shaft Size Type | Imperial |
| Weight | 29 lb |
| UPC Code | 0883450504997 |
| Type E Closed Cover Number | EUC-G |
| Dimension B | 4-1/2 in |
| Dimension H | 8-5/16 in |
| Dimension H1 | 7-3/16 in |
| Dimension H2 | 3.48 in |
| Dimension d1 | 4-23/32 in |
| Dimension A | 2-1/4 in |
| Dimension A1 | 2-1/4 in |
| Housing Width | 3 in |
| Dimension L | 8-1/2 in |
| Dimension L1 | 8 in |
| Dimension L2 | 4.46 in |

| | |
|--|---|
| Dimension Ac | 4.2 in |
| Dimension d2 | 5.65 in |
| e | 0.46 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 1.87 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.26 |
| K Factor | 1.30 |
| C90 Dynamic Load Rating ¹ | 12300 lb |
| C0 Static Load Rating | 61200 lb |
| Fa-max Maximum Permissible Thrust Load ² | 5181 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ³ | 10000 lb |
| Max. Speed ⁴ | 2060 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |