

Timken 306WDD deep groove ball bearings

YOU'LL 129.819 mm Ca FIND AN EXTENSIVE SELECTION OF Timken 306WDD deep groove ball bearings FOR 176.213 mm da SALE. 339.999 mm Da

da	176.213 mm
Da	339.999 mm
Ca	129.819 mm
A1	190.5 mm
A2	273.05 mm
S	4.763 mm
ba	92.869 mm
H	401.637 mm
H1	200.025 mm
H2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J1	114.3 mm
L	711.2 mm
N1	34.925 mm
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
PG	1/4 NPT
h	63.5 mm
Housing	SAW 538
Bearing	23238 CCK/W33

Adapter sleeve assembly	SNW 138×6.15/16
Stabilizing ring	SR-38-32
Labyrinth ring	2 x LOR 155
End plug (suffix Y)	EPR 21
Bearing limiting speed	1800 r/min
P60°	290 kN
P90°	173 kN
P120°	107 kN
P150°	94.3 kN
P180°	113 kN
Pa	68.5 kN
Mass pillow block	172 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g