

# Timken 34275/34492 tapered roller bearings

High Quality Timken 34275/34492 tapered roller bearings. 0.0 Inventory Competitive TIMKEN Manufacturer Name Pricing. Accept Small Order. Easy and Fast Shipping.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 24.97   |
| EAN                       | 0883450306645   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 7/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22220   |
| Seals                     | Triple Lip Urethane   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>100MM Bore; 279.4MM Bolt<br>Circle; 196.85MM Bolt Spacing;<br>1 Piece Solid; C |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Collar   With Set Screw |
| UNSPSC                             | 31171501                                    |
| Harmonized Tariff Code             | 8483.20.40.80                               |
| Noun                               | Bearing                                     |
| Keyword String                     | Flanged                                     |
| Weight / LBS                       | 55  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                       |
| D                                  | 4.59 Inch   116.586 Millimeter              |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                       |
| d                                  | 3.937 Inch   100 Millimeter                 |
| Bolt Spacing                       | 7.75 Inch   196.85 Millimeter               |
| Nominal Bolt Circle Diameter Round | 11 Inch   279.4 Millimeter                  |