

Timken

36690/36620DC+X1S-36690

tapered roller bearings

Browse Timken 36690/36620DC+X1S-36690 tapered roller bearings Categories 35 Outer Diameter (mm) in the Manufacturers Online Free. 15x35x11 Size (mm) including .

| | |
|-------------------------------|----------|
| Size (mm) | 15x35x11 |
| Bore Diameter (mm) | 15 |
| Outer Diameter (mm) | 35 |
| Width (mm) | 11 |
| d | 15 mm |
| D | 35 mm |
| B | 11 mm |
| C | 11 mm |
| ra1 max. | 0,3 mm |
| Angle (α) | 40 ° |
| a | 16 mm |
| r min. | 0,6 mm |
| r1 min. | 0,3 mm |
| 2B | 22 mm |
| da min. | 19,5 mm |
| ra max. | 0,6 mm |
| Db max | 32,5 mm |
| Weight | 0,092 Kg |
| Basic dynamic load rating (C) | 13,6 kN |
| Basic static load rating (C0) | 8,7 kN |

| | |
|---------------------------------|--|
| (Grease) Lubrication Speed | 15 000 r/min |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.091 |
| EAN | 4547359436686 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | Yes |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 40 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 2 (1 Pair) |
| Mounting Arrangement | Duplex-Back to Back |
| Inch – Metric | Metric |
| Long Description | 15MM Bore; 35MM Outside Diameter; 22MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer Item Number | 7202BDB |
| Weight / LBS | 0.2 |

| | |
|------------------|----------------------------|
| Bore | 0.591 Inch 15 Millimeter |
| Width | 0.866 Inch 22 Millimeter |
| Outside Diameter | 1.378 Inch 35 Millimeter |