

Timken 399D/394AS tapered roller bearings

Timken 399D/394AS tapered roller bearings Needs Analysis , 18x20x20 Size (mm) Manufacturing Service . Get Your Free.

Size (mm)	18x20x20
Bore Diameter (mm)	18
Outer Diameter (mm)	20
Width (mm)	20
d	18 mm
D	20 mm
B	20 mm
c1 min	0,1 mm
c2 min	0,2 mm
M	3 mm
Weight	0,0067 Kg
Basic dynamic load rating (C)	43 kN
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B04264
c1 min.	0.1 mm
c1 max.	0.6 mm
c2 min.	0.2 mm
c2 max.	1 mm
$\alpha \pm 8$	20 °
Tolerance shaft	h8

Tolerance housing	H7
Basic dynamic load rating – radial direction C	43 kN
Basic static load rating – radial direction C0	90 kN
Specific dynamic load factor K	120 N/mm ²
Specific static load factor K0	250 N/mm ²
Factor depending on material and bearing type KM	1900
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2.5 m/s
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Mass bushing	0.0067 kg