

Timken 44162/44363D+X2S-44162 tapered roller bearings

We work closely 0.0 Inventory with our Timken 44162/44363D+X2S-44162 tapered roller bearings manufacturing partners to bring TIMKEN Manufacturer Name the best value to customers.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	547 lb
EAN	0013992051752
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	30 Millimeter
Relubricatable	Yes
Insert Part Number	LSE1000BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row Light Duty With Support Wide Inner Ring
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	450.05
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Actual Bolt Center to Center	19.8 Inch 502Millimeter
D	4.803 Inch 122 Millimeter
Nominal Bolt Center to Center	19.8 Inch 502 Millimeter
d	10 Inch 254 Millimeter
B	11.496 Inch 292 Millimeter
Shaft Size	10 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Four-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Standard
Bolt Size	4 x M30
Dimension H	11.496 in
Dimension H1	1.7 in
Dimension H2	23.0 in
Dimension J	19.8 in
Dimension K	5.5 in
Dimension L	27.0 in
Dimension M	9.0 in
Housing Width	8.7 in
Cr – Dynamic Load Rating	167258 lbf
Cor – Static Load Rating	289779 lbf

Ca – Axial Load Rating	12994 lbf
Maximum Speed	820 rpm
Note	This product line was formerly known as “Revolvo”