

Timken 496/492A tapered roller bearings

Enjoy High Margins on Competitive 70x110x20 Size (mm) Pricing.Great Wholesale Products at Low 110 Outer Diameter (mm) Costs.

Size (mm)	70x110x20
Bore Diameter (mm)	70
Outer Diameter (mm)	110
Width (mm)	20
d	70 mm
D	110 mm
B	20 mm
C	20 mm
r min.	1,1 mm
da min.	76,5 mm
da max	80,5 mm
Da max.	103,5 mm
ra max.	1 mm
Weight	0,608 Kg
Basic dynamic load rating (C)	38 kN
Basic static load rating (C0)	31 kN
(Grease) Lubrication Speed	6 000 r/min
(Oil) Lubrication Speed	7 100 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.62

EAN	0029176034350
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	70MM Bore; 110MM Outside Diameter; 20MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6014
Weight / LBS	0.604
Bore	2.756 Inch 70 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
SRI	6.16
hidYobi	6014
LangID	1
D_	110
SREX	0.025
B_	20

da min	76.5
hidTable	ecat_NSRDGB
Oil rpm	7100
SRE	6.16
mass	0.608
GRS rpm	6000
ra	1
SRIX	0.025
D_a	103.5
SRIN	-0.025
C0	31
fo	15.6
SREN	-0.025
DE_	101.906
Prod_Type3	DGBB_SR_OT
DA_	11.906
bomp	0
Z_	14
yobi	6014
C_conv	38000
ALPHA_	0
SDM_	90
r	1.1
KBRG	6101
SBRG	10
DI_	78.094