

# Timken 5205K angular contact ball bearings

Timken 5205K angular contact ball bearings Warehouse offers car parts and car accessories. We ABB MOTORS AND MECHANICAL INC Manufacturer Name sell discount 0.0 Inventory N/A Minimum Buy Quantity online as well as cheap machinery parts.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC                                 |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.82  |
| EAN                       | 0782475119738   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | INS-SXV-014   |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Single Row   Intermediate Duty   Low Base   Narrow Inner Race |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 7/8" Bore; 1-5/16" Base to Center Height; Eccentric Collar Mount; Bal |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P2B-SXVB-014   |
| Manufacturer Internal Number  | 131984   |
| Weight / LBS                  | 1.8  |
| d                             | 0.875 Inch   22.225 Millimeter   |
| B                             | 1.313 Inch   33.35 Millimeter  |
| Bolt Spacing Minimum          | 3.688 Inch   93.675Millimeter  |
| Bolt Spacing Maximum          | 4.5 Inch   114.3Millimeter   |
| D                             | 1.219 Inch   30.963 Millimeter   |
| Nominal Bolt Center to Center | 4.1 Inch   105 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |