

Timken 55187/55443 tapered roller bearings

Timken 55187/55443 tapered roller bearings Engineering Calculator TIMKEN Manufacturer Name , Manufacturing Service . Get Your Free. 0.0 Inventory

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	28.71
EAN	0013992056061
Product Group	B04144
Number of Mounting Holes	2
Mounting Method	Clamp Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	LSE315BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row Light Duty With Support Wide Inner Ring
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80

Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	63.23
Bolt Spacing Minimum	0 Inch 0Millimeter
B	4.921 Inch 125 Millimeter
Nominal Bolt Center to Center	13.9 Inch 354 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
D	3.346 Inch 85 Millimeter
Actual Bolt Center to Center	13.9 Inch 354Millimeter
d	3.938 Inch 100.025 Millimeter
Shaft Size	3-15/16 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Two-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Angled
Bolt Size	2 x M24
Dimension H	125 mm
Dimension H2	265 mm
Dimension J	350 mm
Dimension L	410 mm
Dimension M	120 mm
Housing Width	5.3 in
Cr – Dynamic Load Rating	64745 lbf
Cor – Static Load Rating	82280 lbf
Ca – Axial Load Rating	3596.90 lbf
Maximum Speed	2340 rpm

Note

This product line was formerly known as "Revolvo"