

Timken 559/552DC+X2S-559 tapered roller bearings

The 45x75x16 Size (mm) online Timken 559/552DC+X2S-559 tapered roller bearings parts store gives you immediate access to a selection of more than 1.4 million new, used, remanufactured.

Size (mm)	45x75x16
Bore Diameter (mm)	45
Outer Diameter (mm)	75
Width (mm)	16
d	45 mm
D	75 mm
B	16 mm
C	16 mm
r min.	1 mm
da min.	50 mm
da max	53,5 mm
Da max.	70 mm
ra max.	1 mm
Weight	0,241 Kg
Basic dynamic load rating (C)	20,9 kN
Basic static load rating (C0)	15,2 kN
(Grease) Lubrication Speed	9 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.24
EAN	0029176012938

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 75MM Outside Diameter; 16MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6009VV
Weight / LBS	0.245
Bore	1.772 Inch 45 Millimeter
Outside Diameter	2.953 Inch 75 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
bore diameter:	45 mm
snap ring included:	Without Snap Ring
outside diameter:	75 mm
internal clearance:	C0
overall width:	16 mm
dynamic load capacity:	20900 N

bore type:	Round
precision rating:	ABEC1, P0
closure type:	Double Sealed
finish/coating:	Uncoated
row type & fill slot:	Single Row Non-Fill Slot
cage material:	Steel Cage
SRI	4.52
hidYobi	6009VV
LangID	1
D_	75
SREX	0.02
B_	16
da min	50
hidTable	ecat_NSRDGB
SRE	4.52
mass	0.241
GRS rpm	9000
ra	1
SRIX	0.02
D_a	70
SRIN	-0.02
C0	15.2
fo	15.3
SREN	-0.02
DE_	69.731
Prod_Type3	DGBB_SR_VV
DA_	8.731
bomp	0
Z_	13

yobi	6009VV
C_conv	20900
ALPHA_	0
SDM_	61
r	1
KBRG	6151
SBRG	10
DI_	52.269