

Timken 560-S/552-S tapered roller bearings

Can't find what you're looking for 75 Outer Diameter (mm) for Timken 560-S/552-S tapered roller bearings ? Our expert Representatives be in contact with you 45x75x16 Size (mm) shortly!

| | |
|---------------------|----------|
| Size (mm) | 45x75x16 |
| Bore Diameter (mm) | 45 |
| Outer Diameter (mm) | 75 |
| Width (mm) | 16 |
| d | 45 mm |
| D | 75 mm |
| B | 16 mm |
| C | 16 mm |
| a | 16 mm |
| d1 | 55,7 mm |
| r1 min. | 1 mm |
| r2 min. | 1 mm |
| r3 min. | 0,6 mm |
| r4 min. | 0,6 mm |
| D1 | 64,3 mm |
| da min. | 49,6 mm |
| Da max. | 70,4 mm |
| db min | 49,6 mm |
| ra max. | 1 mm |
| rb max. | 0,6 mm |
| dh | 8,2 mm |

| | |
|-------------------------------|--------------|
| Db max | 70,8 mm |
| Weight | 0,24 Kg |
| Basic dynamic load rating (C) | 13 kN |
| Basic static load rating (C0) | 8,5 kN |
| (Grease) Lubrication Speed | 27 000 r/min |
| (Oil) Lubrication Speed | 41 000 r/min |