

Timken 595/592D+X2S-595 tapered roller bearings

How do I place an EMERGENCY order for a Timken 595/592D+X2S-595 tapered roller bearings SKF Manufacturer Name 3.0 Inventory that I want to pick up at a our store?

Inventory	3.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.183
EAN	7316571743417
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	No
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	25MM Straight Bore; 52MM Outside Diameter; 18MM Width; C0-Medium Clearance; Shaft Mount; Double Row
UNSPSC	31171510
Harmonized Tariff Code	84823080

Noun	Bearing
Keyword String	Spherical
Weight / LBS	0.403
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
D	2.047 Inch 52 Millimeter
d	0.984 Inch 25 Millimeter
B	0.709 Inch 18 Millimeter
bore diameter:	25 mm
operating temperature range:	0 °F to 185 °F
outside diameter:	52 mm
cage material:	Steel
overall width:	18 mm
bearing material:	Steel
bore type:	Straight
cage type:	Inner Ring Guided
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	C0
application:	Metal manufacturing, Paper mills, Steel mills—plate, slab, strip, blast furnace, Overhead crane
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	18 mm
dynamic load capacity:	11218 lbf
fillet radius:	1 mm
static load capacity:	9892 lbf

series:	222
maximum rpm:	17000 RPM