

Timken 659/654D+X1S-659 tapered roller bearings

Enjoy High Margins on 170 Outer Diameter (mm) Competitive Pricing.Great Wholesale Products at 95x170x32 Size (mm) Low Costs.

Size (mm)	95x170x32
Bore Diameter (mm)	95
Outer Diameter (mm)	170
Width (mm)	32
d	95 mm
D	170 mm
B	32 mm
C	32 mm
a	5,69 mm
b	3,65 mm
f	3,05 mm
r min.	2,1 mm
r0 max.	0,6 mm
r1 min.	0,5 mm
D1	163,65 mm
D2	182,9 mm
da min.	106 mm
Da max.	159 mm
Weight	2,62 Kg
Basic dynamic load rating (C)	109 kN
Basic static load rating (C0)	81,9 kN
(Grease) Lubrication Speed	3700 r/min

(Oil) Lubrication Speed	4400 r/min
Bearing No.	6219NR
r(min)	2.1
r1(min)	0.5
Cr	136
C0r	81.9
Cu	4.65
f0	14.4
Grease lub.	3700
Oil lub.	4400
D2(min)	182.9
f(0}0.05)	3.05
da(min)	106
Da(max)	159
Dx(min)	185
Cy(max)	8.44
ra(max)	2
rb(max)	0.5
(Refer.) Mass (kg)	2.62