

Timken 66187/66462 tapered roller bearings

What are the dimensions of a SKF Manufacturer Name Timken 66187/66462 tapered roller bearings? Manufacturing Service N/A Minimum Buy Quantity . Get Your Free, Instant 0.0 Inventory Quote

| | |
|-----------------------------|----------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 251.999 |
| EAN | 7316571680538 |
| Product Group | M06110 |
| Bearing (basic designation) | C 3156 K |
| Adapter sleeve | 0H 3156 HTL |
| Locating ring | 2 x FRB 10/460 |
| da | 260 mm |
| d2 | 398 mm |
| Ca | 166 mm |
| Da | 460 mm |
| A | 320 mm |
| A1 | 280 mm |
| ATS | 330 mm |
| ATK | 425 mm |
| H | 551 mm |
| H1 | 280 mm |
| H2 | 105 mm |
| J | 670 mm |

| | |
|-------------------------------------|-----------|
| J1 | 160 mm |
| L | 790 mm |
| N | 50 mm |
| N1 | 42 mm |
| s | 16 mm |
| ba min. | 119 mm |
| ba max. | 149 mm |
| bb | 114 mm |
| bc | 154.5 mm |
| J6 | 740 mm |
| N4 max. | 20 mm |
| Labyrinth seal | 2 x TS 56 |
| Taconite seal | 2 x TK 56 |
| End cover | ETS 56 |
| P0° | 4000 kN |
| P55° | 5000 kN |
| P90° | 2400 kN |
| P120° | 1800 kN |
| P150° | 1600 kN |
| P180° | 2000 kN |
| Pa | 1300 kN |
| Q120° | 2860 kN |
| Q150° | 1650 kN |
| Q180° | 1430 kN |
| Mass housing | 252 kg |
| Cap bolt, size | M 30×200 |
| Cap bolt, rec. tightening torque | 400 N·m |
| Appropriate attachment bolt, size G | 36 mm |

| | |
|---|----------|
| Appropriate attachment bolt, rec. tightening torque | 2280 N·m |
| Eye bolt, size | 2 x M 24 |
| Initial grease fill, 20% | 2.9 kg |
| Initial grease fill, 40% | 4.4 kg |
| Lock nut | HM 44 T |
| Lock washer | MB 44 |
| db | 240 mm |