

Timken 67388D/67322+Y1S-67322 tapered roller bearings

Our N/A Minimum Buy Quantity highly-skilled and factory-trained service SKF Manufacturer Name experts have the resources to help you with all your Timken 67388D/67322+Y1S-67322 tapered roller bearings needs – including routine maintenance, major repairs, warranty service, and equipment 0.0 Inventory inspections.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.204
EAN	7316577042019
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric

Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	50MM Bore; Straight Bore Profile; 110MM Outside Diameter; 27MM Width; Polymer Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ 310 ECP/C3
Weight / LBS	2.652
D	4.331 Inch 110 Millimeter
B	1.063 Inch 27 Millimeter
d	1.969 Inch 50 Millimeter
bore diameter:	50 mm
static load capacity:	112 kN
outside diameter:	110 mm
precision rating:	Not Rated
overall width:	27 mm
maximum rpm:	8000 RPM
flanges:	(2) Outer Ring, (1) Inner Ring
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring

outer ring width:	27 mm
operating temperature range:	Maximum of +300 °F
fillet radius:	2 mm
dynamic load capacity:	127 kN
series:	NJ3