## Timken 71412/71750-B tapered roller bearings

With over 10170 full-service stores, our Timken 71412/71750-B tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time 0.0 Inventory and your TIMKEN Manufacturer Name hard-earned N/A Minimum Buy Quantity dollars.

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 64 lb   |
| EAN                       | 0013992041319   |
| Product Group             | B04144  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Clamp Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Cylindrical Roller Bearing                                  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 24 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | LSM85BX   |
| Seals                     | Triple Lip Labyrinth  |
| Housing Configuration     | 2 Piece Split   |
| Inch — Metric             | Metric  |
| Other Features            | Single Row   Light Duty   With<br>Support   Wide Inner Ring |

| UNSPSC                        | 31171511                                    |
|-------------------------------|---|
| Harmonized Tariff Code        | 8483.20.40.80                               |
| Noun                          | Bearing                                     |
| Keyword String                | Pillow Block                                |
| Weight / LBS                  | 55.04                                       |
| Nominal Bolt Center to Center | 12.6 Inch   320 Millimeter                  |
| Actual Bolt Center to Center  | 12.6 Inch   320Millimeter                   |
| В                             | 4.409 Inch   112 Millimeter                 |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter                        |
| D                             | 2.953 Inch   75 Millimeter                  |
| d                             | 3.346 Inch   85 Millimeter                  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter                        |
| Shaft Size                    | 85 mm                                       |
| Seal Type                     | Aluminium Triple Labyrinth                  |
| Bearing Type                  | Split Cylindrical Expansion<br>Type         |
| Support Type                  | Two-Bolt Plummer Block                      |
| Series Type                   | Light Series                                |
| Pillow/Plummer Block Style    | Split Cylindrical Housed Unit —<br>Standard |
| Bolt Size                     | 2 x M24                                     |
| Dimension H                   | 4.409 in                                    |
| Dimension H1                  | 1.7 in                                      |
| Dimension H2                  | 9.9 in                                      |
| Dimension J                   | 12.6 in                                     |
| Dimension L                   | 15.0 in                                     |
| Dimension M                   | 3.5 in                                      |
| Housing Width                 | 5.4 in                                      |
| Cr — Dynamic Load Rating      | 42039 lbf                                   |

| Cor — Static Load Rating | 51931 lbf  |
|--------------------------|--|
| Maximum Speed            | 2790 rpm   |
| Note                     | This product line was formerly<br>known as "Revolvo" |