

# Timken 7330WN MBR angular contact ball bearings

YOU'LL FIND 100.013 mm da 200 mm Da AN EXTENSIVE SELECTION 62.789 mm Ca OF Timken 7330WN MBR angular contact ball bearings FOR SALE.

da	100.013 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	231.775 mm
S	4.763 mm
ba	50.006 mm
H	239.316 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAF 522
Bearing	22222 EK

Adapter sleeve assembly	SNW 22×3.15/16
Stabilizing ring	SR-22-19
Taconite seal	TER 109
End plug (suffix Y)	EPR 13
Max. speed for Taconite seal	775 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	17.3 kN
Mass pillow block	33.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g