

Timken 759/753 tapered roller bearings

We Open Enclosure Provide Extensive Double Row Configuration Timken 759/753 tapered roller bearings Selection And Competitive Wholesale Cylindrical Bore Bore Type Pricing.

| | |
|-------------------------|---------------------|
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Double Row |
| Roller Profile | Symmetric |
| Center Guidance | Floating Steel Ring |
| Retainer Material | Pressed Steel |
| Nr. of Holes | 4 |
| Weight | 3.840 kg |
| d | 110 mm |
| D | 170 mm |
| B | 45 mm |
| Fillet Radius/Chamfer | 2 mm |
| Groove Width A | 9 mm |
| Hole Diameter (do) | 5 mm |
| Dynamic Load Rating | 415,000 N |
| Static Load Rating | 475,000 N |
| Limiting Speed – Grease | 3,000 rpm |
| Limiting Speed – Oil | 3,800 rpm |
| Constant e | 0.24 |
| Axial Load Factor Y0 | 2.78 |
| Axial Load Factor Y1 | 2.84 |
| Axial Load Factor Y2 | 4.23 |

| | |
|------------------|-------------------|
| Radial Clearance | 0.120 to 0.160 mm |
| da (min) | 120 mm |
| Da (max) | 160 mm |
| ra (max) | 2 mm |