

Timken 775/774D+X2S-775 tapered roller bearings

Request A Quote For Your Special 100x125x13 Size (mm) Timken 775/774D+X2S-775 tapered roller bearings Needs Today! Free 125 Outer Diameter (mm) Quotes. ISO 9001 certified.

| | |
|--|---|
| Size (mm) | 100x125x13 |
| Bore Diameter (mm) | 100 |
| Outer Diameter (mm) | 125 |
| Width (mm) | 13 |
| di – 100 mm / Tolerance: K6+0,004 / -0,018 | 100 mm / Tolerance: K6+0,004 / 0,018 |
| Da – 125 mm / Tolerance: h6 -0,025 | 125 mm / Tolerance: h6 0,025 |
| H – 13 mm / Tolerance: +/-0,12 | 13 mm / Tolerance: +/-0,12 |
| Di | 112,5 mm |
| DM | 112 mm |
| da | 111,5 mm |
| h – 13 mm / Tolerance: E8 -0,01 | 13 mm / Tolerance: E8 0,01 |
| rmin | 1 mm |
| S | 1,2 mm |
| m | 0,5 kg / Weight |
| sr min | 0,005 mm / Min. radial bearing clearance |
| sr max | 0,020 mm / Max. radial bearing clearance |

| | |
|----------------------|---|
| sk min | 0,010 mm / Min. axial tilting clearance |
| sk max | 0,04 mm / Max. axial tilting clearance |
| RL0max | 0,008 mm / Low clearance: Preload |
| VSPmin | 0,005 mm / Min. bearing preload |
| VSPmax | 0,020 mm / Max. bearing preload |
| Ca | 27000 N / Dynamic load rating (axial) |
| C0a | 102000 N / Static load rating (axial) |
| Cr | 19400 N / Dynamic load rating (radial)(for radial load only) |
| C0r | 40500 N / Static load rating (radial)(for radial load only) |
| nG 0l | 680 1/min / Limiting speed for oil lubrication with preload |
| nG Fett | 680 1/min / Limiting speed for grease lubrication with normal clearance |
| Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.599 |
| EAN | 4012802368772 |
| Product Group | B00234 |