

# Timken 861/854B tapered roller bearings

Timken 861/854B tapered roller bearings Warehouse offers car parts and car accessories. We sell discount online as well 52×25.4×44.4 Size (mm) as cheap machinery parts.

Size (mm)	52×25.4×44.4
Bore Diameter (mm)	52
Outer Diameter (mm)	25,4
Width (mm)	44,4
d	25.4 mm
D	52 mm
B1	44.4 mm
C	15 mm
d1	33.74 mm
d2	37.4 mm
B	34.9 mm
B4	4.75 mm
r1,2 – min.	0.6 mm
s1	26.9 mm
Basic dynamic load rating – C	14 kN
Basic static load rating – C0	7.8 kN
Fatigue load limit – Pu	0.335 kN
Limiting speed with shaft tolerance h6	1500 r/min
Calculation factor – f0	14
Mass bearing	0.23 kg
Thread – G2 – 1/4-28 UNF	1/428 UNF
Hexagonal key size for grub screw – H	3.175 mm

d1 ≈	33.74 mm
r1,2 min.	0.6 mm
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Limiting speed1)	1500 r/min
Calculation factor f0	14
Mass complete bearing	0.23 kg
Thread grub screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m
Rubber seating ring	RIS 205