

Timken

94700/94114CD+X6S-94700

tapered roller bearings

YOU'LL FIND 0.0 Inventory N/A Minimum Buy Quantity AN EXTENSIVE SKF Manufacturer Name SELECTION OF Timken 94700/94114CD+X6S-94700 tapered roller bearings FOR SALE.

| | |
|---------------------------|--------------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 9.99 |
| EAN | 7316576668111 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 1213 EK |
| Seals | Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Double Row Medium Duty |

| | |
|--------------------------------|--|
| Long Description | 2 Bolt Pillow Block; 2-3/16" Bore; 3" Base to Center Height; Tapered Adapter Sleeve Mount; |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SAF 1513 |
| Weight / LBS | 22 |
| Bolt Spacing Minimum | 8.125 Inch 206.375Millimeter |
| B | 3 Inch 76.2 Millimeter |
| Nominal Bolt Center to Center | 8.8 Inch 223 Millimeter |
| d | 2.188 Inch 55.575 Millimeter |
| D | 4.5 Inch 114.3 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| Bolt Spacing Maximum | 9.5 Inch 241.3Millimeter |
| bore diameter: | 2.1875 in |
| overall width: | 4.5000 in |
| overall length: | 11.0000 in |
| seal type: | Labyrinth Seal |
| overall height: | 5.8125 in |
| base height: | 1.0000 in |
| mounting: | Two-Bolt Base |
| maximum operating temperature: | Max 210 °F |
| bearing type: | Spherical Roller |
| maximum rpm: | 7000 rpm |
| bore type: | Round |
| lubrication type: | Lubrication Fitting |

| | |
|----------------------------|-----------------------------------|
| housing construction: | Split Pillow Block |
| bolt size: | 0.7500 in |
| base to bore centerline: | 3.0000 in |
| series: | SAF1513 |
| housing material: | Cast Iron |
| replacement bearing: | 1213 EKTN9 |
| locking device: | Adapter Mount |
| weight: | 23.1 lbs |
| bearing material: | Cast Iron |
| manufacturer product page: | Click here |
| finish/coating: | Blue Alkyd/Acryl Paint (RAL 5001) |
| manufacturer upc number: | 7316576668111 |
| da | 55.563 mm |
| Da | 120 mm |
| Ca | 39.014 mm |
| A1 | 79.375 mm |
| A2 | 114.3 mm |
| ba | 27.781 mm |
| H | 147.637 mm |
| H1 | 76.2 mm |
| H2 | 25.4 mm |
| J min. | 206.375 mm |
| J max. | 241.3 mm |
| L | 279.4 mm |
| N1 | 19.05 mm |
| R1 | 44.45 mm |
| R2 | 15.875 mm |
| RG | 1/8 NPT |

| | |
|--|----------------|
| PG | 1/8 NPT |
| h | 30.163 mm |
| Housing | SAF 513 |
| Bearing | 1213 EKTN9 |
| Adapter sleeve assembly | SNW 13×2.3/16 |
| Stabilizing ring | 2 x SR-13-0 |
| Labyrinth ring | 2 x LER 29 |
| End plug (suffix Y) | EPR 6 |
| Bearing limiting speed | 7000 r/min |
| P60° | 50.3 kN |
| P90° | 30.2 kN |
| P120° | 17.8 kN |
| P150° | 16 kN |
| P180° | 19.1 kN |
| Pa | 4.45 kN |
| Mass pillow block | 10.5 kg |
| Cap bolt | 2 x 1/2-13 UNC |
| Cap bolt recommended tightening torque | 81.3 N·m |
| Cap bolt, SAE grade | 5 |
| Appropriate attachment bolt size G | 0.625 in |
| Initial grease fill | 107.73 g |