

# Timken 99600/99098X tapered roller bearings

Can't find what 136.525 mm da you're looking for Timken 99600/99098X tapered roller bearings ? Our expert Representatives be in contact with you shortly!

da	136.525 mm
Da	289.999 mm
Ca	89.789 mm
A1	158.75 mm
A2	225.425 mm
S	4.763 mm
ba	70.644 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SAFS 532
Bearing	22232 CCK/W33

Adapter sleeve assembly	SNW 32×5.3/8
Stabilizing ring	SR-32-0
Labyrinth ring	2 x LOR 129
End plug (suffix Y)	EPR 16
Bearing limiting speed	2800 r/min
P60°	345 kN
P90°	207 kN
P120°	133 kN
P150°	120 kN
P180°	145 kN
Pa	38.5 kN
Mass pillow block	129 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g