

# Timken ARZ 17 40 79 needle roller bearings

Enjoy High 100 Outer Diameter (mm) Margins on Competitive 140x100x25 Size (mm) Pricing.Great Wholesale Products at Low Costs.

Size (mm)	140x100x25
Bore Diameter (mm)	140
Outer Diameter (mm)	100
Width (mm)	25
d	100 mm
D	140 mm
T	25 mm
d1	119.2 mm
B	25 mm
C	20 mm
r1,2 – min.	1.5 mm
r3,4 – min.	1.5 mm
a	24 mm
da – max.	109 mm
db – min.	107 mm
Da – min.	131 mm
Da – max.	131 mm
Db – min.	135 mm
Ca – min.	5 mm
Cb – min.	5 mm
ra – max.	1.5 mm
rb – max.	1.5 mm

Basic dynamic load rating – C	119 kN
Basic static load rating – C0	204 kN
Fatigue load limit – Pu	22.4 kN
Reference speed	3200 r/min
Limiting speed	4800 r/min
Calculation factor – e	0.33
Calculation factor – Y	1.8
Calculation factor – Y0	1
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
UNSPSC	31171516
Weight / Kilogram	0
Product Group	B04334