

Timken GE110SX plain bearings

offers a Timken GE110SX plain bearings selection of Genuine 39×42.862×14 Size (mm) at Wholesale Prices. We are a Timken GE110SX plain bearings Certified Parts Retailer

Size (mm)	39×42.862×14
Bore Diameter (mm)	39
Outer Diameter (mm)	42,862
Width (mm)	14
d	42.862 mm
A1	39 mm
A2	14 mm
J	105 mm
L	137 mm
T	54.2 mm
H	15.9 mm
B	49.2 mm
s1	30.2 mm
Basic dynamic load rating – C	33.2 kN
Basic static load rating – C0	21.6 kN
Limiting speed	140 r/min
Limiting temperature – T	350 °C
Mass bearing unit	2.25 kg
Grub (set) screw – G2 – 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw – H	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.23
EAN	7316571381251
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	9/16 Inch
Relubricatable	Yes
Insert Part Number	YAR 209-111-2FW/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-11/16" Bore; 5.8" Bolt Circle; 4-1/8" Bolt Spacing; 1 P
Other Features	Single Row Standard Duty Wide Inner Race Open End High Temperature Bearing with Graphite H
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing

Keyword String	Flanged
Manufacturer Item Number	FY 1.11/16 TF/VA228
Weight / LBS	4.9
Nominal Bolt Circle Diameter Round	5.8 Inch 148 Millimeter
Bolt Spacing	4.125 Inch 104.78 Millimeter
Bore	1.688 Inch 42.875 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Length Thru Bore	1.938 Inch 49.225 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
bore diameter:	1.6875 in
radial static load capacity:	4860 lbf
bolt center-to-center length:	105 mm
seal type:	Contact Seal
overall length/diameter:	137 mm
length through bore:	54.2 mm
bore type:	Round
operating temperature range:	-30 to +120 °F
mounting type:	Four-Bolt Flange
finish/coating:	Uncoated
housing material:	Cast Iron
lubrication type:	Cannot Be Relubricated
locking device:	Set Screw
series:	FY
expansion type:	Non-Expansion Bearing (Fixed)
manufacturer upc number:	7316571381251

N	15.9 mm
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Attachment bolts, recommended metric size G	14 mm
Bearing	YAR 209-111-2FW/VA228